

BGS 50AU

- Double skin door
- 2 wash cycles - 120/180 seconds
- Door safety switch
- Built-in rinse-aid dispenser
- Built-in detergent dispenser
- Pump out drain



BGS 50AU

BGS 50AU - Technical Data

| | BGS 50AU |
|--|-------------|
| Rack/hour - Cesti/ora - Cestos/hora (n°) | 30 / 20 |
| Washing cycles - Cicli di lavaggio - Ciclos de lavado (s) | 120 / 180 |
| Power supply - Alimentazione elettrica - Alimentacion electrica | 240V ~ 50Hz |
| Washing pump - Pompa di lavaggio - Bomba de lavado (W) | 530 |
| Boiler heating element - Resistenza boiler - resistencia calentador (W) | 2800 |
| Tank heating element - Resistenza vasca - Resistencia cuba (W) | 2700 |
| Total capacity - Assorbimento totale - Absorcion total (W) | 3330 |
| Tank capacity - Capacità vasca - Capacidad cuba (W) | 26 |
| Boiler capacity - Capacità boiler - Capacidad calentador (l) | 5.7 |
| Water consumption - Consumo acqua - Consumo de agua (l) | 3 |
| Basket size - Dimensioni cesto - Dimensions da cesta (mm) | 500 x 500 |
| Glass max height - Massima altezza bicchieri - Maximo alto vajillas (mm) | 320 |
| Dishes max height - Massima altezza piatti - Maximo alto platos (mm) | 345 |
| Tray max height - Massima altezza vassoi - Maximo alto bandejas (mm) | - |
| Pression hydric pressure - Pressione idrica - Presion aqua (kPa) | 200+400 |
| Rinse aid dispenser - Dosatore brillantante - Dosificador para abrillantador | STANDARD |
| Detergent dispenser - Dosatore detersivo - Dosificador paa detergent | OPTIONAL |
| Drain pump - Pompa di scarico - Bomba de descargo | STANDARD |

SUPPLIED WITH

- 1 x Cup rack
- 1 x Plate rack
- 1 x Cutlery container

BGS 50AU - Installation Drawings

