


## A72 TNN

ADVANCE A72 700 Lt -2+8°C 1 door

### REFRIGERATED CABINET



### FUNCTIONS

Temperature range	<b>-2° + 8°</b>
Energy label	<b>B</b>
Climatic class	<b>5</b>
Hot gas	

### BASIC TECHNICAL DATA

Net width (mm)	<b>700</b>
Net depth (mm)	<b>830</b>
Net height (mm)	<b>2080</b>
Opening door depth 90° (mm)	<b>1472</b>
Net weight (Kg)	<b>117</b>
Capacity (lt)	<b>562</b>
Distance between grids (mm)	<b>55</b>
Electrical power	<b>230/1/50</b>
Elec. Power** (W)	<b>295</b>
Max absorbed current (A)**	<b>1,1</b>
Cooling power (W)	<b>294</b>
Consumption (kWh/Kg) ISO16825 (W24h)	<b>0,97</b>
NOISE LEVEL [dB(A)]	<b>46</b>
Cooling liquid (Gas)	<b>R290</b>
External width (mm)	<b>760</b>
Packing depth (mm)	<b>860</b>
External height (mm)	<b>2220</b>
Gross weight (Kg)	<b>130</b>

### CONNECTIONS FOR REMOTE UNITS

UR Net weight (Kg)	<b>117</b>
--------------------	------------

### MAIN FEATURES

- Inside and outside in stainless steel
- Printed guide supports
- 83 mm wall insulation with CFC-free polyurethane
- Dashboard that can be opened to facilitate periodic maintenance (cleaning the condenser)
- Touch screen control
- Cell interior with rounded corners to facilitate cleaning
- Height-adjustable 150 mm steel feet
- Automatic defrosting with resistance and dissipation of condensation water through hot gas
- Doors with self-closing hinges
- Light for room lighting and lock as standard
- Predisposition for positioning on a plinth
- Monobloc buffer, external to the cell, with forced ventilation from top to bottom
- Internal set-up: 3 plastic coated GN2/1 grids

### SET UP

3 plastic grids GN 2/1	
Compartments number	<b>1</b>
Door number	<b>0</b>
Halfdoor number	<b>2</b>