

OVENS

Code RGV051M **Model** RGV051M



GAS COMBI OVEN DIRECT STEAM GENERATION - ELECTRO MECHANICAL CONTROL - 5 GN1/1

General characteristics



SPEEDY COMBI M

Technical/functional characteristics

Electromechanical with temperature switch adjustable 70-300°C
Manual humidifier, oven chamber vent valve, oven lights. Control light.

OPTIONAL: Hand shower.

OPERATING MODES

- Convention 70 - 300°C
- Convention with humidifier
- Steam 70 - 100°C
- Convention / steam combi mode 70 - 300°C

FUNCTIONS

- Timed cooking
- Continuous cooking

Technical Data

| Dimensions | |
|-------------------------------|------|
| Width (mm) | 870 |
| Depth (mm) | 640 |
| Height (mm) | 595 |
| Gas connection (Ø) | - |
| Electric connection (V/~ /HZ) | 230 |
| Cold water connection (Ø) | 3/4" |
| Hot water connection (Ø) | - |

| Cold soft water connection (Ø) | |
|--------------------------------|-------|
| Drain (Ø) | 40 mm |
| Gas power (KW) | 8.5 |
| Electric power (KW) | 0.25 |
| Plate dimensions (mm) | - |
| Tank capacity (Lt) | - |
| TANK DIMENSIONS | - |
| Internal ovens dimension(mm) | - |

OVENS

Code RGV051M **Model** RGV051M



GAS COMBI OVEN DIRECT STEAM GENERATION - ELECTRO MECHANICAL CONTROL - 5 GN1/1

| Code | Description |
|--------|--|
| RKKV51 | STAINLESS STEEL AXTRACTION HOOD WITH MOTOR AND AIR-COOLED STEAM CONDENSER |
| PL002 | NEBULIZE FOR CLEANSER |
| RPS | LEFT HINGED DOOR EXTRA COST |
| Cd002 | STAINLESS STEEL TROLLEY TO HOLD COMPLETE WASCHING SYSTEM CAPACITY 2 TANKS OF 10 LT |
| PL005 | NEBULIZE FOR CLEANSER - 5 LT |
| RSP071 | STAINLESS STEEL OVENS FLOOR STAND WITH SIDE RUNNERS 8 GN1/1 |
| dL010 | ALKALINE CLEANSER (TANK 10 LT) |
| RAC071 | STAINLESS STEEL HOLDING CABINET WITH ELECTROMECHANICAL CONTROLS |
| RSR071 | STAINLESS STEEL OVENS FLOOR STAND |
| KSA001 | NEEDLE-CORE TEMPERATURE SENSOR FOR VACUUM COOKING - Ø 1 MM |
| RKD071 | SHELF FOR CLEANSER TANK FOR RSR/RSP STANDS |
| LD25 | SHOWER FOR OVEN CAVITY WITH STAINLESS STEEL HOSE, FITTING AND CONNECTIONS |