



Cucimax | Tilting Braising Pans

It's an indispensable piece of equipment for the food industry and for the most advanced centralised kitchens: the high versatility of its use allows one to optimize the production processes and human resources, reducing consumption and saving money. With the innovative CUCIMAX bratt pan with mixer you can now cook under pressure and mix at the same time.

The best in tilting braising pans

This multifunctional cooker is complete, innovative and sturdy, ideal for countless applications. Among the equipment for professional kitchens, Cucimax is really one of the most versatile and evolved, since it allows different types of preset cooking: steaming, boiling, pressure cooking, braising and browning.

DIRECT ELECTRIC HEATING NON PRESSURISED

MODEL	CAPACITY lt	POWER kW	DIMENSIONS mm	NOTES
CBTE 090 V1	90	13.5	1445 x 1290 x 1030H	3N + PE AC 400V 50/60 Hz
CBTE 130 V1	130	13.5	1455 x 1290 x 1030H	
CBTE 180 V1	180	21	1665 x 1505 x 1030H	
CBTE 310 V1	310	29	1755 x 1560 x 1030H	




Cucimax can be used for

- Bolognese sauce/pasta sauces
- Stew
- Mirepoix
- Risottos
- Polenta
- Caramel
- Jams and marmalades
- Vegetable stew
- Sautéed vegetables


boiling | **braising** | pasteurising | **tilting** | **mixing** | cooling | frying | underpressure | vacuum cooking | cutting | washing | drying

TECHNICAL DRAWING MOD. **CBTE 090 V1**




E	Potenza assorbita Electric power	Elektrische Leistung Puissance électrique	13.50 (kW)
E	Collegamento Elettrico Electric connection	Elektrische Verbindung Connexion électrique	380-415V 3N ~ 50/60Hz
A	Allacciamento Acqua Calda Hot water inlet	Warmwasseranschluss Raccordement eau chaude	3/4"
B	Allacciamento Acqua Fredda Cold water inlet	Katlwasseranschluss Raccordement eau froide	3/4"

TECHNICAL DRAWING MOD. CBTE 130 V1




E	Potenza assorbita Electric power	Elektrische Leistung Puissance électrique	13.50 (kW)
E	Collegamento Elettrico Electric connection	Elektrische Verbindung Connexion électrique	380-415V 3N ~ 50/60Hz
A	Allacciamento Acqua Calda Hot water inlet	Warmwasseranschluss Raccordement eau chaude	3/4"
B	Allacciamento Acqua Fredda Cold water inlet	Kaltwasseranschluss Raccordement eau froide	3/4"

TECHNICAL DRAWING MOD. CBTE 180 V1



E	Potenza assorbita Electric power	Elektrische Leistung Puissance électrique	21.00 (kW)
E	Collegamento Elettrico Electric connection	Elektrische Verbindung Connexion électrique	380-415V 3N ~ 50/60Hz
A	Allacciamento Acqua Calda Hot water inlet	Warmwasseranschluss Raccordement eau chaude	3/4"
B	Allacciamento Acqua Fredda Cold water inlet	Kaltwasseranschluss Raccordement eau froide	3/4"

TECHNICAL DRAWING MOD. CBTE 310 V1



E	Potenza assorbita Electric power	Elektrische Leistung Puissance électrique	29.00 (kW)
E	Collegamento Elettrico Electric connection	Elektrische Verbindung Connexion électrique	380-415V 3N ~ 50/60Hz
A	Allacciamento Acqua Calda Hot water inlet	Warmwasseranschluss Raccordement eau chaude	3/4"
B	Allacciamento Acqua Fredda Cold water inlet	Kaltwasseranschluss Raccordement eau froide	3/4"