

RETARDER PROOFER CABINET - TEMP. -2/+35 °C - 560 LT

Model: FEN1



Technical/functional Characteristics

- External panels in AISI 304 18/10 stainless steel (Scotch-Brite satin-finish).
- External back panel in electro-galvanised steel.
- External base panel in electro-galvanised steel.
- Inner lining with rounded corners in AISI 304 18/10 stainless steel.
- Die-formed leakproof floor ledge.
- Insulation in high density (42 kg/m3 approx.) expanded polyurethane, 60 mm thick, HCFC-free.
- Copper evaporator coil aluminium fins protected against corrosion with non-toxic paint finish, using electrolytical process Paint-finished steel condenser coil, with high thermal efficiency Anti-condensation heating element on the body below the magnetic seal stop.
- Balancing heater to have low humidity and high temperature Door in AISI 304 18/10 stainless steel (Scotch-Brite stain-finish).
- Ergonomic handle across entire width of door and magnetic seals on all 4 sides of the door.
- Self-closing doors locking in open position at 100°.
- Stainless steel feet Ø with adjustable H 150 ÷180 mm.

TECHNICAL DATA

DIMENSIONS	
WIDTH (MM)	740
DEPTH (MM)	730
HEIGHT (MM)	2070
CAPACITY	-
DIMENSIONE CELLA (MM)	-
TEMPERATURA DI LAVORO	-

ELECTRIC CONNECTION (V/~/HZ)	220
COLD WATER CONNECTION (Ø)	-
DRAIN (Ø)	-
POTENZA FRIGORIFERO	-
ELECTRIC POWER (KW)	750
CAPACITA' ABBATTIMENTO +90/+3 °C (KG)	-
CAPACITA' CONGELAMENTO +90/-18 °C (KG)	-

ACCESSORIES
