




	WATER CONNECTION 3/4" GAS
	DRAIN PIPE Ø 24mm
	ELECTRICAL SUPPLY

TECHNICAL DATA		STANDARD			
EXTERNAL DIMENSIONS					
width		600 mm			
depth		680 mm			
height		860 mm			
WEIGHT		67.5 kg			
VOLTAGE		400V 3N 50Hz			
POWER EQUIRED		6650 W			
WATER HARDNESS		2-8 °F			
INLET WATER PRESSURE		200 - 400 kPa			
CROCKERY DIMENSIONS					
plates diameter		400 mm			
dishes max. height		400 mm			
RACK DIMENSIONS		500 x 500 mm			
RACK EQUIPMENT		1 x spatula basket - 1 x mesh basket - 1 x tray support			
WASHING CYCLES (secs)	1(90)	2(120)	3(180)	4(300)	
WATER SUPPLY 55°C					
rack/h(*) ⁽¹⁾	40	30	20	12	
WATER SUPPLY 10°C					
rack/h(*) ⁽¹⁾	25	25	20	12	
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	2.3 L				
BOILER CAPACITY	5.7 L				
BOILER HEATING ELEMENT	6000 W				
RINSING TEMPERATURE (SET)	85 °C				
TANK CAPACITY	16.5 L				
TANK HEATING ELEMENT	2700 W				
TANK TEMPERATURE (SET)	55 °C				
PUMP POWER	650 W (340 L/min ^{***})				
DRAIN PUMP (optional)	25 W h max draining 0.8 m (40 L/min ^{***})				
NOISE	61.3±0.7 dB(A)				

(*) STANDARD THERMOSTOP

(***) MAXIMUM FLOW RATE

¹⁾ In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash -cycle total timing might result longer than set.