


GCR202 STD

GCR202 Trolleys: 1 x GN 2/1 (600x800)

BLASTCHILLERS



FUNCTIONS:

Blast chilling cycles +3° HARD/SOFT,

Shock freezing cycles -18° HARD/SOFT,

Blast chilling yield (+3°C)/Kg **160**

Shock freezing yield (-18°C)/Kg **120**

Climatic class **4**

Consumption (kWh/Kg) EN17032 **0,02**

DATI TECNICI DI BASE

Net width (mm) **1700**

Net depth (mm) **1530**

Net height (mm) **2230**

Net weight (Kg) **570**

N° trays GN1/1 (535x325) or 600x400 **2 GN1/1 - 600X400**

N° trays GN2/1 (530x650) or 600x800 **1 GN2/1 - 600X800**

Electrical power **380-420/3/50 + N**

Elec. Power** (W) **795**

Max absorbed current (A)** **2,11**

compressor (HP) **8**

Freon (Gas) **R452A**

External width (mm) **2350**

Packing depth (mm) **1700**

External height (mm) **1900**

Gross weight (Kg) **700**

MAIN FEATURES

Full Touch 7-inch Display

Panel construction capacity GN 1/1, GN2/1, 600x400,



600x800

Finely "Scotch Brite" satined exterior

80 mm insulation thickness in CFC and HCFC-free PU, density 42 kg/m3

Floor thickness 60 mm

Large storage capacity cell featuring rounded corners for easy cleaning

Ergonomic handles

Front electric panel that can be fully inspected

ID Master Descr Ord Lung Prof Alte DimFisse DimNonFM LMin LMax PMin PMax HMin HMax Articolo ArticoloDx Senso FileGrafica P1 P2 GruppoEsecuz Prezzo SupplemFisso FattoreMoltiplica VarPrezzoLung VarPrezzoProf VarPrezzoAlte PrezzoPerimetro PerimVarPrezzoLung PerimVarPrezzoProf PerimVarPrezzoAlte sFlag Commento 6953 ScorrEstAtlante Anta Infinity Scorr Esterna Atlante 80 775 26 2299 100 775 26 26 100 2299 LIN0_0600PHE Sx/Dx Falso Falso Falso Falso Falso Falso A Anta INFINITY ESTERNA 6957 ScorrEstAtlant

Air distribution with new evaporator deflector

OPTIONAL electronic expansion valve

PLUS versions ventilation regulation by inverter

Connectivity 4.0

Load capacity pursuant to EN17032

OPTIONAL weather sealed and soundproofed condensing units

Internal set-up: 8 plastic grids GN2/1 + 4 MIDDLE GRIDS

ALLESTIMENTI

Heated Multipoint probe

202 (C40) "S"

