

	WATER CONNECTION 3/4" GAS
	DRAINING PIPE Ø 24mm
	ELECTRICAL SUPPLY

TECHNICAL DATA		STANDARD			
EXTERNAL DIMENSIONS					
width		450 mm			
depth		535 mm			
height		700 mm			
WEIGHT		37 kg			
VOLTAGE		240V 50Hz			
POWER REQUIRED		3200 W			
WATER HARDNESS		2-8 °F			
INLET WATER PRESSURE		200 - 400 kPa			
CROCKERY DIMENSIONS					
plates diameter		295 mm			
dishes max. height		305 mm			
RACK DIMENSIONS		400 x 400 mm			
RACK EQUIPMENT		2 x glass basket - 1 x saucer holder - 1 x cutlery container			
WASHING CYCLES (secs)		1(60)	2(90)	3(120)	4(180)
WATER SUPPLY 55°C					
rack/h(*) ⁽¹⁾		60	40	30	20
WATER SUPPLY 10°C					
rack/h(*) ⁽¹⁾		16	16	16	16
WATER CONSUMPTION / CYCLE (water pressure 200kPa)		1.8 L			
BOILER CAPACITY		3.4 L			
BOILER HEATING ELEMENT		2800 W			
RINSING TEMPERATURE (SET)		85 °C			
TANK CAPACITY		14.5 L			
TANK HEATING ELEMENT		1250 W			
TANK TEMPERATURE (SET)		55 °C			
PUMP POWER		400 W (185 L/min ^{***})			
DRAIN PUMP (optional)		25 W h max draining 0.8 m (40 L/min ^{***})			
NOISE		60.6[CF] 61.2[LS] (db(A)±0.7)			

(*) STANDARD THERMOSTOP

(***) MAXIMUM FLOW RATE

¹⁾ In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash -cycle total timing might result longer than set.