

# MODULINE

*foodfinish & foodserve technologies*

## HOLDING SYSTEMS

### HHB128E

#### Static holding trolley



#### CONSTRUCTION FEATURES

- Tightness chamber with radius corners
- Rubber bumpers
- Total thermic insulation with rock or glass wool
- Long lasting front and door seals made up of food grade of high heat resistance
- Double door to reduce mostly the drop in temperature at opening
- Removable side racks to facilitate cleaning
- Static heating provided by low consumption wise heating element that covers up all the chamber
- Snap-shut doors
- Mounted on four 150 mm diameter castors, two of which with brake
- Ergonomic handles for pushing and guiding
- Easy access to facilitate maintenance and repair

#### FUNCTIONAL FEATURES


- Electronic control of the temperature
- Operating temperature 30°±120°C
- Two adjustable humidity vents on the door
- Chamber with safety thermostat

#### STANDARD SUPPLY

- Two shelves with grid GN2/1 each door

#### OPTIONS & ACCESSORIES

- Stainless steel plate baskets
- Additional shelves with grid GN2/1
- Guides for gastronorm containers



# MODULINE


*foodfinish & foodserve technologies*

## HOLDING SYSTEMS



- A ON/OFF switch
- B Temperature increase key
- C Temperature decrease key
- D Display
- E START/STOP key

### TECHNICAL INSTALLATION DIAGRAM



Model	Overall dimensions (W x D x H) - mm	Trays capacity	Plates capacity ø260	Plates capacity ø320	Power kW	Power supply
<b>HHB128E</b>	1170 x 855 x 1820 h	16 x GN 2/1 32 x GN 1/1	128	96	2,25	AC 230 V / 50 Hz