

REFRIGERATED COUNTER SUPREME 18 - 3 DOORS

TEMP. -2 °C/+8 °C

Model: KST18-03



Technical/functional Characteristics

They are made of stainless steel and feature polished, corner-free interiors. The exteriors have a fine scotch-brite satin finish. The insulation is 60 mm thick and made of high-density expanded polyurethane which is totally free of CFC.


Main feature

- Refrigerant TN R134a BT R452a.
- Removable condenser unit;
- Easy access to electrical and electronic components;
- Automatic defrosting device;
- Pressed cabinet bottom with rounded corners and removable shelf holders, for the highest ease of cleaning and loading flexibility.
 - Ventilated refrigeration system (The evaporator is painted and equipped with a protection casing);
 - Removable dust filter

TECHNICAL DATA

DIMENSIONS	
WIDTH (mm)	1730
DEPTH (mm)	690
HEIGHT (mm)	810
CAPACITY	256
CABINET DIMENSIONS (mm)	1030x570x550
RANGE OF TEMPERATURE	-2/+8

ELECTRIC CONNECTION(V/-/Hz)	220
COLD WATER CONNECTION (Ø)	-
DRAIN (Ø)	-
COOLING POWER W	418
ELECTRIC POWER(W)	420



ACCESSORIES

KIT 2 DRAWERS H(INT)=120 + 330 MM - ACCESSORY
3 SIDE KICK PLATE
KIT 3 DRAWERS H(INT)=120 MM - ACCESSORY
S/S stainless steel GRID GN1/1
KIT WHEELS
RILSAN GRID GN1/1
TOP FOR REFRIGERATED COUNTER
LOCK FOR DOOR OR SINGLE DRAWER
KIT 2 DRAWERS H(INT)=240 MM - ACCESSORY
TOP WITH BACKSPLASH FOR REFRIGERATED COUNTER