

## KST 84

800L four door confectionery table without working top

### functions

|                   |                  |
|-------------------|------------------|
| Temperature range | <b>-2 / +8°C</b> |
| Energy label      | <b>C</b>         |

### technical data

|                                     |                 |
|-------------------------------------|-----------------|
| Width (mm)                          | <b>2486</b>     |
| Depth (mm)                          | <b>790</b>      |
| Height (mm)                         | <b>850</b>      |
| Weight (kg)                         | <b>240</b>      |
| Capacity (L)                        | <b>800</b>      |
| N° trays 1/1GN (535x325) or 600x400 | <b>32</b>       |
| Electric connection (V/~/Hz)        | <b>230/1/50</b> |
| Electric power (W)                  | <b>335</b>      |
| Cooling power (W)                   | <b>277</b>      |
| Internal width (mm)                 | <b>1756</b>     |
| Internal depth (mm)                 | <b>670</b>      |
| Internal height (mm)                | <b>600</b>      |
| Gross weight (kg)                   | <b>260</b>      |
| Noise level [dB(A)]                 | <b>&lt; 70</b>  |
| Refrigerant type (gas)              | <b>R134A</b>    |



### main features

- The CONFECTIONERY series refrigerated tables with electronic control, ventilated, are constructed internally and externally in AISI 304 18/10 stainless steel.
- Single frame construction, capacity EN.
- PU, HCFC free insulation, thickness 50 mm, density 42 kg/m3.
- Environmentally-friendly R134a / R452A gas.
- Automatic defrosting and evaporation device condensate water without electricity input.
- Large storage capacity cells featuring rounded corners for easy cleaning.
- Ergonomic handles and magnetic seals on 4 sides.
- Feet (Ø 2") with adjustable height 150 ÷ 200 mm in
- AISI 304 18/10 steel.
- Self-closing doors with 100° opening lock and reversibility with accessory kit.
- Stainless steel snap-on rack supports and uprights, removable with no need to use tools for easier cleaning operations.
- Power supply voltage 230V / 1Ph / 50Hz



