

MS 081 E

Static holding trolley



CONSTRUCTION FEATURES

- Tightness chamber with radiuses corners
- Plastic bumpers
- Total thermic insulation with rock or glass wool
- Long lasting front and door seals made up of food grade of high heat resistance
- Removable side racks to facilitate cleaning
- Static heating provided by low consumption wise heating element that covers up all the chamber
- Snap-shut door
- Mounted on four 125 mm diameter castors, two of which with brake
- Ergonomic handle for pushing and guiding
- Easy access to facilitate maintenance and repair

FUNCTIONAL FEATURES


- Electronic control of the temperature
- Operating temperature 30°-120°C
- Two adjustable humidity vents on the door
- Chamber with safety thermostat

STANDARD SUPPLY

- Removable GN 1/1 tray racks

OPTIONS & ACCESSORIES


- No



M O D U L I N E

food service




HOLDING SYSTEMS



Electronic control

- A ON/OFF switch
- B Temperature increase key
- C Temperature decrease key
- D Display
- E START/STOP key

TECHNICAL INSTALLATION DIAGRAM



| Model | Overall dimensions (W x D x H) - mm | Trays capacity | Power kW | Power supply |
|-----------------|--|----------------|-------------|------------------|
| MS 081 E | 550 x 740 x 1000 h | 8 x GN 1/1 | 1,00 | AC 230 V / 50 Hz |

