

## 2 ZONE ELECTRIC RANGE WITH CERAMIC GLASS PASS THROUGH - TOP VERSION

### General characteristics

1100 Pass-Through Line is characterized by its versatility, its perfect modules matching and their sturdiness, thanks to the 2 mm thick cooking tops in s/s AISI 304 cut with laser. All these features allow to assemble central cooking blocks on specific customers' request. Reliability and high efficiency are granted by tested components and high performances of heating elements. Stands can be equipped with pass-through ovens, heated, ventilated, neutral, either suspended or cantilever cupboards. Appliances in compliances with CE standards.



### CERAMIC GLASS RANGE

### Technical/functional characteristics

- Outer casing in s/s 18/10 and Schotch Brite finishing.
- Top with thickness 2mm.
- Shaped cooker control panel with knobs slanted towards the operator.
- Waterproof and shatterproof ceramic glass hob.
- Square 270x270mm cooking area display, indicating ideal pan size.
- 4 kW power for each individual cooking zone.
- Thermostatically-controlled temperature range from 70 to 450°C.
- Heat mode activation light and residual heat indicator light.

### Technical Data

Dimensions	
Width (mm)	450
Depth (mm)	1100
Height (mm)	280
Gas connection (Ø)	-
Electric connection (V/~ /HZ)	400V/3N
Cold water connection (Ø)	-
Hot water connection (Ø)	-

Cold soft water connection (Ø)	-
Drain (Ø)	-
Gas power (KW)	-
Electric power (KW)	8
Plate dimensions (mm)	-
Tank capacity (Lt)	-
TANK DIMENSIONS	-
Internal ovens dimension(mm)	-

# SERIE GIANO

**Code** CR1010449    **Model** N1100PC/VCE450



## 2 ZONE ELECTRIC RANGE WITH CERAMIC GLASS PASS THROUGH - TOP VERSION

