

RI 140 PT C PRED

2 pass through doors - Capacity per compartment: 2 GN1 / 1, 1 GN2 / 1, 1 600X400, 1 600X800
REFRIGERATED / FREEZER CABINET

functions

Temperature range	-30 / +18°C
Energy label	C
Climatic class	5

technical data

Width (mm)	2000
Depth (mm)	1330
Height (mm)	2365
Weight (kg)	190
Opening door depth 90° (mm)	2050
Capacity (L)	3447
N° trolleys 1/1GN (535x325)	2
N° trolleys 600x400	1
N° trolleys 2/1GN (535x650)	1
N° trolleys 600x800	1
Electric connection (V/~ /Hz)	230/1/50
Electric power (W)	1160
Max. absorbed current (A)	8
Cooling power (W)	2760
Noise level [dB(A)]	<70
Refrigerant type (gas)	R290A

connections for remote units

Connections max distance (mt)	15
Connections / Liquid line Ø (mm)	6
Connections / Suction line Ø (mm)	10
Connections / Electrical cables from condensing unit to cabinet (n°x mm²)	(2+1) X 1.5



main features

- Pass-through refrigerated cabinet
- Capacity of the wheeled containers: GN 2/1 or EN
- 400x600 mm or 600x800 mm
- Finely SCOTCH-BRITE satined exterior
- PU, CFC and HCFC free insulation, thickness 80 mm
- Connectivity IOT 4.0 (optional)
- Automatic defrost and condensate evaporation device without the need for any electricity
- Large capacity makes it possible to insert trolleys up to overall dimensions: 700x900x1860 mm
- Ergonomic full height handles and magnetic seals on 4 sides
- Capacity suitable for RATIONAL trolleys
- Self-closing doors with 100° opening lock
- Insulated floor in AISI 304 18/10 steel for the C version
- Bumpers on the back and inside of the door in stainless steel
- Refrigerated versions (built-in condensing unit), prepared versions (without condensing unit) with or without remote unit supplied by us

set up

Compartments number	1
Door number	2

