


RI BT COMPACT

RI COMPACT

REFRIGERATED CABINET



FUNCTIONS

Temperature range	-15° -20°
Climatic class	5
Hot gas	

BASIC TECHNICAL DATA

Net width (mm)	850
Net depth (mm)	970
Net height (mm)	2350
Opening door depth 90° (mm)	1725
Net weight (Kg)	210
Capacity (lt)	878
N° teglie GN1/1 (535x325)	1 trolleys
N° teglie 600x400	1 trolley
N° teglie GN2/1 (530x650)	1 trolley
N° teglie 600x800	-
Electrical power	230/1/50
Elec. Power** (W)	860
Max absorbed current (A)**	3,9
Cooling power (W)	1369
NOISE LEVEL [dB(A)]	<70db
Freon (Gas)	R290a
Freon quantity (g)	150
External width (mm)	940
Packing depth (mm)	1060
External height (mm)	2500
Gross weight (Kg)	232

MAIN FEATURES

Monocoque construction COMPACT version

Capacity of the wheeled containers: GN 2/1 or EN 400x600 mm

Finely SCOTCH-BRITE satined exterior

PU, CFC and HCFC free insulation, thickness 70 mm

Bidirectional IOT 4.0 connectivity (optional)

Automatic defrost and condensate evaporation device without the need for any electricity

Large capacity cell allows the introduction of trolleys with maximum dimensions: 660x800x1860 mm

Ergonomic full height handles and magnetic seals on 4 sides

40mm Insulated floor in AISI 304 Stainless steel for the BT version

Internal bumper on all sides

SET UP

Compartments number	1
Door number	1

