

RI BT

1170L one door roll in refrigerated cabinet -20 / -15°C

functions

Temperature range	-20 / -15°C
Climatic class	5

technical data

Width (mm)	880
Depth (mm)	1070
Height (mm)	2250
Weight (kg)	200
Opening door depth 90° (mm)	1850
Capacity (L)	1170
N° trolleys 1/1GN (535x325) or 600x400	2
N° trolleys 2/1GN (535x650) or 600x800	1
Electric connection (V/~/Hz)	230/1/50
Electric power (W)	955
Max. absorbed current (A)	5.4
Cooling power (W)	848
Compressor (HP)	1 1/4
Internal width (mm)	700
Internal depth (mm)	900
Internal height (mm)	1860
Refrigerant type (gas)	R452A



main features

- Panel construction (monocoque Mod.ROLL-INDX 1 TN COMPACT / ROLL-INDX 1 BT COMPACT).
- Capacity of the wheeled containers: GN 2/1 or EN 400x600 mm or 600x800 mm.
- Finely SCOTCH-BRITE sated exterior.
- PU, CFC and HCFC free insulation, thickness 80 mm (60 mm Mod. ROLL-INDX 1 TN COMPACT / ROLL-INDX 1 BT COMPACT), density 42 kgm3 (back insulation 60mm).
- Automatic defrost and condensate evaporation device without the need for any electricity.
- Large capacity cell makes it possible to insert trolleys up to overall dimensions: 700x900x1860 mm.
- Ergonomic full height handles and magnetic seals on 4 sides.
- Standard lock with key.
- Self-closing doors with 100° opening lock.
- AISI 304 18/10 steel insulated floor for the LT version.
- Bumper on back and door interior in plastic material.
- Refrigerated versions (built-in condensing unit), versions without condensing unit with or without remote unit supplied by us.
- Versions with glass door.

