

## T18-03 710 PRED

279L three door refrigerator without working top remote unit

### functions

|                   |                  |
|-------------------|------------------|
| Temperature range | <b>-2 / +8°C</b> |
| Energy label      | <b>B</b>         |
| Climatic class    | <b>5</b>         |

### technical data

|                                      |                 |
|--------------------------------------|-----------------|
| Width (mm)                           | <b>1392</b>     |
| Depth (mm)                           | <b>690</b>      |
| Height (mm)                          | <b>860</b>      |
| Weight (kg)                          | <b>89</b>       |
| Opening door depth 90° (mm)          | <b>1080</b>     |
| Capacity (L)                         | <b>279</b>      |
| Distance between runners (mm)        | <b>120</b>      |
| N° trays 1/1GN (535x325) or 600x400  | <b>15</b>       |
| Electric connection (V/~/Hz)         | <b>230/1/50</b> |
| Electric power (W)                   | <b>240</b>      |
| Cooling power (W)                    | <b>418</b>      |
| Consumption (kWh/kg) ISO16825 (W24h) | <b>2.31</b>     |
| Internal width (mm)                  | <b>1080</b>     |
| Internal depth (mm)                  | <b>570</b>      |
| Internal height (mm)                 | <b>600</b>      |
| Gross weight (kg)                    | <b>106</b>      |
| Noise level [dB(A)]                  | <b>&lt; 70</b>  |
| Refrigerant type (gas)               | <b>R134A</b>    |



### main features

- BODY DEPTH = 690 mm.
- HEIGHT = 710 mm.
- Insulation thickness 60 mm, refrigerant R134A.
- Fully extractable drawers thanks to the special stainless steel telescopic slides.
- Pressed cabinet bottom with rounded corners and removable shelf holders, for the highest ease of cleaning and loading flexibility.
- The evaporator is foamed into the backwall of the cabinet and is equipped with automatic condensate evaporation system.
- Gas: TN=R143a / BT=R452a



