

## TP 240Q

633L 9 x 1/4 GN Refrigerated Pizza Table

### functions

|                   |                   |
|-------------------|-------------------|
| Temperature range | <b>+0 / +10°C</b> |
| Climatic class    | <b>5</b>          |

### technical data

|                               |                 |
|-------------------------------|-----------------|
| Width (mm)                    | <b>1960</b>     |
| Depth (mm)                    | <b>800</b>      |
| Height (mm)                   | <b>1470</b>     |
| Net weight (kg)               | <b>347</b>      |
| Capacity (L)                  | <b>633</b>      |
| Distance between runners (mm) | <b>55</b>       |
| N° pans 1/4GN (162x265)       | <b>9</b>        |
| Electric connection (V/~ /Hz) | <b>230/1/50</b> |
| Electric power (W)            | <b>280+130</b>  |
| Cooling power (W)             | <b>304+111</b>  |
| Noise level [dB(A)]           | <b>&lt;70</b>   |
| Refrigerant type (gas)        | <b>R134A</b>    |
| Gross weight (kg)             | <b>409</b>      |



### main features

- Single frame construction. Capacity EN.
- PU, HCFC free insulation, thickness 50 mm, density 42 kg/m3.
- Environmentally-friendly R134a / R452A gas.
- Automatic defrost and condensate evaporation device without the need for any electricity.
- Large storage capacity cells featuring rounded corners for easy cleaning.
- Ergonomic handles and magnetic seals on 4 sides.
- Feet (Ø 2") with adjustable height 150 ÷ 200 mm in AISI 304 18/10 steel.
- Self-closing doors with 100° opening lock and reversibility with accessory kit.
- Snap-on Rack supports and uprights in stainless steel, that can be extracted with no need to use tools for easier cleaning.
- Power supply voltage 230V / 1Ph / 50Hz

