

**CODICE**  
BN20ES980135

**MODELLO**  
LS82V

**PRODUCT**  
REFRIGERATED CABINETS



### TECHNICAL SPECIFICATIONS

Monocoque construction with internal and external finishing in stainless steel

60 mm insulation in high density polyurethane foam approx. 42 kg/m<sup>3</sup> without HCFC

60 mm thick insulation in HCFC-free polyurethane foam with density approx. 42 kg/m<sup>3</sup>

Adjustment of relative humidity (RH%) by means of a special probe and steam generator

Monoblock sistem on the ceiling, designed to allow 100% inter usable space

Forced and controlled ventilation cooling system to assure maximum efficiency and uniformity in the whole cell of the generated microclimate

Automatic defrosting cycles for energy savings

Control able to maintain the correct internal humidity of the cell from 30/95% of RH

Microprocessor control with air probe, evaporator probe, condenser probe and RH% probe for total monitoring of operation of the season cabinet

Microprocessor control equipped with cell probe, evaporator probe, condenser probe and RH% probe for total monitoring of the proper functioning of the seasoner

Internal equipment: 4 GN 2/1 stainless steel grids, 4 "C" guide pairs, 4 meat hangers, humidity probe

## SERIE MATORATO

**CODICE**  
 BN20ES980135

**MODELLO**  
 LS82V

**PRODUCT**  
 REFRIGERATED CABINETS

**Technical Information**

SPECIFICATION	DATA
MATERIAL	BN20ES980135
DIM. WIDTH	790 mm
DIM. DEPTH	1030 mm
DIM. HEIGHT	2110 mm
NET WEIGHT	171 Kg
CELL SIZE	620X735X1510
PACKAGE LENGTH	880 mm
PACKAGE WIDTH	760 mm
PACKAGING HEIGHT	2220 mm
PACKAGE VOLUME	1,485 m³
GROSS PACKING WEIGHT	195 Kg
STANDARD POWER SUPPLY	220-240 V ~ 50 Hz
ELECTRICAL POWER	1634 Kw
TOTAL ABSORPTION	5.3
TENSION	220-240 V ~ 50 Hz
REFRIGERANT POWER	594 W
GAS/REFRIGERANT TYPE	R290
GAS QUANTITY	150 g.
CLIMA CLASS	5
CAPACITIES	607 l.
TEMPERATURE RANGE	-5 / +30°C
DEPTH WITH OPEN DOOR	1700 mm

**CODICE**  
 BN20ES980135

**MODELLO**  
 LS82V

**PRODUCT**  
 REFRIGERATED CABINETS

**ACCESSORIES**

CODE	MODELLO	DESCRIZIONE
990443	LS CG "C"	Seasoner cabinet "C" GUIDE pair
1440065530	GR PLAST GN2/1	PLASTIC COATED GRID 530X650 MM GN2/1
1440165530	LS GR INOX GN2/1	STAINLESS GRID 530X650 MM GN2/1
FR6130671	LS82 AS	ROD FOR SEASONER CABINET HOOK RACK
990032	LS82 KG	KIT 10 SEASONER CABINET HOOKS
KIT-IOT 4.0	KIT-IOT 4.0	CONNECTIVITY 4.0 SUPREME SUPPLEMENT KIT