

CODICE
GC401

MODELLO
GC401

PRODUCT
BLAST CHILLERS



SERIE TROLLEY BLAST FREEZER

TECHNICAL SPECIFICATIONS

MAIN FEATURES

Full Touch 7-inch Display

The control software allows quick, easy and intuitive selection of the following operating modes:

Positive chilling from +90°C to +3°C at core temperature, with SOFT and HARD cycles

Storage at +3°C

Rapid freezing from +90°C to -18°C at core temperature, with SOFT and HARD cycles

Storage at -18°C

The multifunctional USB port, supplied as standard, enables fast and secure management of operations, supporting firmware updates, import and export of parameters, recipes and languages. It also provides efficient downloading of HACCP data (including temperatures, alarms and events), ensuring traceability and full regulatory compliance.

Finely "Scotch Brite" satined exterior

80 mm insulation thickness in CFC and HCFC-free PU, density 42 kg/m³

Floor thickness 60 mm

Evaporator heat exchanger made of copper and aluminium, treated with protective cathodic coating based on non-toxic epoxy resin, side-mounted. It is equipped with an opening cover operated by a dedicated safety key, ensuring easy, correct and safe maintenance operations.

Ergonomic handles

Front electric panel that can be fully inspected

Drain plug

Ventilation regulation by inverter

Magnetic door closure, ensuring automatic, safe and reliable closing even under intensive operating conditions.

Evaporator installed inside the cold room, floor-suspended to facilitate cleaning operations and ensure optimal hygiene.

Sandwich floor with reinforced structure, featuring a 30/10 steel plate with non-slip 5WL finish.

BLAST CHILLER CELL 4 GN1/I TROLLEYS - 1 DOOR - REMOTE CONDENSING UNIT OPTIONAL

CODICE
GC401
Technical Information

MODELLO
GC401

PRODUCT
BLAST CHILLERS

SPECIFICATION	DATA
MATERIAL	GC401
DIM. WIDTH	1300 mm
DIM. DEPTH	4100 mm
DIM. HEIGHT	2100 mm
NET WEIGHT	1725 Kg
CELL SIZE	740x3640x1820
VOLUME (net)	11.193
GROSS PACKING WEIGHT	1840 Kg
STANDARD POWER SUPPLY	380-420/3Ph+N/50hz
ELECTRICAL POWER	34600W Kw
REFRIGERANT POWER	54840 W
GAS/REFRIGERANT TYPE	R452A
CAPACITIES	4 carrelli GN1/I - EN1 I.
INSULATION THICKNESS	80 mm
Chilling yield (+90°=> +3°) Kg	320
Freezing yield (+90°=> -18°) Kg	320
DOOR OPEN DIMENSION	740 x 1820 mm

**BLAST CHILLER CELL 4 GN1/I TROLLEYS - 1
DOOR - REMOTE CONDENSING UNIT
OPTIONAL**

CODICE

GC401

OPTIONAL

MODELLO

GC401

PRODUCT

BLAST CHILLERS

	MODELLO	DESCRIZIONE
	PVEE	ELECTRONIC EXPANSION VALVE

**BLAST CHILLER CELL 4 GN1/1 TROLLEYS - 1
DOOR - REMOTE CONDENSING UNIT
OPTIONAL**

CODICE

GC401

ACCESSORIES

MODELLO

GC401

PRODUCT

BLAST CHILLERS

CODE	MODELLO	DESCRIZIONE
R-GCX01	R-GCX01	STAINLESS STEEL RAMP FOR TROLLEY INSERTION FOR GN 1/1 COLD ROOMS – WITH DRAIN OUTLET
GMR401	GMR401	AIR-COOLED REMOTE CONDENSING UNIT FOR COLD ROOM GC401 – REFRIGERANT R452A – POWER SUPPLY 380–420V / 3PH+N / 50HZ – TMAX = 38°C, TMIN = –10°C
GMR401-CS	GMR401-CS	ENCLOSED AND SOUND-ATTENUATED MOTOR FOR GC401 AIR-COOLED UNIT - R452A - 380-420V / 3-phase + neutral / 50Hz - Operating range: +38°C to -10°C
KIT-IOT 4.0	KIT-IOT 4.0	CONNECTIVITY 4.0 SUPREME SUPPLEMENT KIT