

ORACRBXL

HIGH SPEED OVEN - ALL IN ONE. COMBI WAVE / HIGH SPEED OVEN - BOOSTED VERSION (COLOUR RED. RAL 3020)



Features



HIGH SPEED OVEN

An operating mode that simultaneously uses convection, microwave and impingement modes, with temperatures from 100°C to 300°C.



FAST COOKING SYSTEM

Rely on our know-how with automatic, tried-and-tested recipes for high-speed cooking in High Speed Oven mode.



COMBI WAVE

In Combi Wave mode, the high speed oven can be used as a convection oven with temperatures from 30°C to 300°C, as a microwave oven with power up to 2000 W or with a combination of the two cooking methods to achieve results that always exceed expectations.



MICROWAVE COOKING SYSTEM

Rely on our know-how by using the automatic, tried-and-tested recipes for cooking in Combi Wave mode.



CONNECTED

Oracle connects free-of-charge to Lainox's Nabook plus portal via the standard- supply Wi-Fi and ethernet features giving you a 4.0 kitchen (find out more on nabookplus.cloud).



OWB - ORACLE WASHABLE BOX

A special Teflon oven chamber which can be removed and washed for the next round of cooking, making the cleaning procedure fast and cost-effective.



OOS - ORACLE ODORLESS SYSTEM

A labyrinth baffle catalyst filter containing platinum particles which help to reduce steam, odours and grease residue during cooking. The Oracle Odorless System does not require any cleaning or routine maintenance work. Its efficiency is always guaranteed.

Capacity			
Capacity	Red - 36,4 lt.		
Dimensions			
Width	mm	577	22.7
Depth	mm	797	31.4
Height	mm	630	24,8
Maximum outer width	mm	467	18.4
Max exterior depth	mm	657	25.9
Maximum exterior height	mm	630	24.8
Packaging width	mm	990	39.0
Packing depth	mm	770	30.3
Packaging height	mm	800	31.5
Net weight	kg	74	163.2
Gross weight	kg	86	189.6
Volume	m3	0.29	10.2
Packing volume	m3	0.61	21.5
Cooking compartment width	mm	460	18.1
Cooking compartment depth	mm	440	17.3
Cooking chamber height	mm	180	7.1
Support base width	mm	536	21.1
Support base depth	mm	646	25.4
Power plug configuration	IEC 309		
Cable length	m	2	6.56
Technical Data			
High Speed Oven temperature	°C	100 / 300	NaN
Temperatura Combi Wave	°C	30 / 300	NaN
Power supply			
Power supply voltage	3N-AC 400 V		
Electrical absorption	A	18	
Frequency	Hz	50	
Total electric power	kW	6	
Microwave	kW	2	
Impingement	kW	3	

Emissions	
Latent heat	W 450
Sensitive heat	W 346
Noisiness	db < 70

OPTIONAL ELECTRIC CONFIGURATION, WITHOUT EXTRA CHARGE - TO BE REQUESTED WHEN ORDERING

Option code	Connection plug (Plug provided)	Cable length (Provided - mt.)	Power supply voltage	Frequency Hz	Total electric power		Power output - kW		Country		
					kW	A	Impingement	Microwave			
OR380	Not included	2	3N-AC 380 V	60	6	18	3	2	KSA/KO/LATAM		
OR3230	Not included	2	3-AC 230 V	60	6	18	3	2	LATAM		
OR3208	Not included	2	3-AC 208 V	60	6	20	3	2	LATAM		
OR32305	Not included	2	3-AC 230 V	50	6	18	3	2	W		
OR3093	IEC 309 - 32 A	2	1N-AC 230 V	50	6	26	3	2	EU		
AUS	Australia	EU	Europe	KO	South Korea	KSA	Kingdom of Saudi Arabia	LATAM	Latin America	UK	United Kingdom

HOW TO USE

- Combi Wave. - MCS (Microwave Cooking System) automatic cooking system for Italian and international recipes, including the history, ingredients, cooking accessories, procedure and automatic cooking program. - Manual mode with three instant start cooking methods: convection, microwave or combined convection + microwave.
- High Speed Oven. - FCS (Fast Cooking System) automatic cooking system for Italian and international recipes, including the history, ingredients, cooking accessories, method and automatic cooking program. - Manual mode with instant start.
- Programmable mode: possibility of programming and storing a recipe with its cooking procedures in automatic sequence.

CONNECTIVITY

- Nabook Plus - Thanks to the Cloud feature, it is possible to access Nabook Plus, the virtual kitchen assistant (read more on nabookplus.cloud, free registration).
- Direct access to the recipe database with download option (patented).
- Synchronisation of multiple Oracle ovens connected to the same account (patented).
- HACCP Monitoring.
- Remote diagnosis through the Nabook plus portal by the LAINOX Service Center.
- Possibility to download recipes from the Nabook Plus portal based on country.
- Possibility to run automatic software updates on multiple devices simultaneously.
- Wi-Fi connection. Compatible with IEEE 802.11g (2.4 GHz) standard.
- Automatic software update notification system.
- Recipe creation including ingredients with procedure and photo.

CONTROL MECHANISMS

- USB connection to download HACCP data, update software and upload/download cooking recipes.
- Possibility of choosing the fan speed.
- Automatic fan speed for High Speed Oven mode.

STRUCTURAL CHARACTERISTICS

- Pull-down door with ergonomic handle.
- The door slides under the oven cooking surface, allowing the food to be removed safely without the risk of burns.
- Integrated catalyst filter for operation without hood.
- Perfectly smooth room.

OPERATION

- High-definition 7-inch capacitive LCD color screen with choice of "Touch Screen" functions.
- Organisation of recipes in folders with preview, giving each folder its own name.
- Display that can be configured based on the needs of the user, bringing forward the programmes used most.
- Oracle coach. Virtual assistant that provides advice on using and informs when maintenance is needed.
- There are about 30 recipes available in Oracle and a growing number of alternative ones are available via access to the Nabook plus portal. Each recipe has been tested to guarantee best results.
- Rapid cooling of the cooking chamber with open door.
- Possibility of preheating the cooking chamber up to 300°C.
- Starting an automatic "One Touch" cooking.
- User interface with a choice of 29 languages.

SAFETY FEATURES

- Compliant with the IEC60335-1, IEC60335-2-90 and EMC international standards.
- Max 65°C external temperature on the door panel.
- Self-diagnosis with smart error viewing.
- Door open/closed electronic sensor.

CLEANING AND MAINTENANCE

- Easy external cleaning thanks to the perfectly smooth surfaces and IPX3 protection rating against water spray.
- OWB - Oracle Washable Box. special removable and washable box chamber.

INSTALLATION AND ENVIRONMENT

- Quality ISO 9001 / Safety ISO 45001 / Environmental ISO 14001 certification.
- Product recycling rate: 90%.
- 100% recyclable packaging.

STANDARD EQUIPMENT

- Wi-Fi connection. Compatible with IEEE 802.11g (2.4GHz) standard
- USB connection
- Ethernet connection
- Anodized aluminum alloy plate
- Oracle Washable Box
- Oracle Washable Door Cover. Removable and washable inner door protection
- Aluminium peel
- Electric plug
- Power cable - 2 m
- Humidity management plugs

OPTIONAL TO BE REQUESTED WHEN ORDERING

- OR380:** Optional electric configuration, without extra charge. 3N-AC 380-400 V - 60 Hz. Plug not included
- OR3230:** Optional electric configuration, without extra charge. 3-AC 230 V - 60 Hz. Plug not included
- OR3208:** Optional electric configuration, without extra charge. 3-AC 208 V - 60 Hz. Plug not included
- OR32305:** Optional electric configuration, without extra charge. 3-AC 230 V - 50 Hz. Plug not included
- OR3093:** Optional electric configuration, without extra charge. 1N-AC 230 V - 50 Hz. Plug included (IEC 309 - 32 A)
- SOWBHDx:** Extra charge for Oracle Washable Box Heavy Duty version OWBHDx. Replaces the standard model



A	Technical compartment cooling air intake				
			Equipotential connection		USB connection
					Ethernet connection